



TRUCKS

A Toyota Group Company

HINO **e**

ELECTRIC TRUCKS



HINO | e

ELECTRIC TRUCKS



OVERALL FEATURES

- STANDARD CHARGING PROVIDED THROUGH TYPE 1, LEVEL 2 SINGLE PHASE (208/240 VAC) UP TO 19.2 kW
- CHARGER IS SAE J1772 COMPLIANT
- OPTIONAL FAST CHARGING PROVIDED THROUGH STANDARD CCS TYPE 1 LEVEL 3, DC FAST CHARGING UP TO 80 kW

M5e

GVWR	19,500 LBS
Type	Permanent Magnet AC Motor
Continuous Power	110 HP (80 kW)
Maximum Power	170 HP (125 kW)
Maximum Torque	1,110 LB-FT (1,500 Nm)
Battery Capacity	138 kWh
Cell Type	Lithium-Ion (LiNiMnCoO ₂)
Additional	V2G Capable
Charging Time	Up to 8 Hours



L6e

GVWR	25,950 LBS.
Type	Permanent Magnet AC Motor
Continuous Power	270 HP (200 kW)
Maximum Power	335 HP (250 kW)
Maximum Torque	2,580 LB-FT (3,500 Nm)
Battery Capacity	220 kWh
Cell Type	Lithium-Ion (LiNiMnCoO ₂)
Additional	V2G Capable
Charging Time	Up to 12 Hours



Legal Disclaimer
 The equipment and specifications shown are subject to change without notice. The information, content, and materials are presented "as is" at the time of publication, and no representations are made that the content is error-free. ©Hino Motors Sales U.S.A., Inc. All rights reserved. All other marks are trademarks of their respective owners.

